

Led Fluorescent Light

NO.	Shell	Mode	L(mm)	Mode	Power(W)	Lumen(LM)	Power Factor	Input voltage(V)
1	Glass tube	SPT-GS10-600-6	600	T10	6	≥480	≥0.9	85V-264V
2		SPT-GS10-600-8	600	T10	8	≥640	≥0.9	85V-264V
3		SPT-GS10-900-10	900	T10	10	≥800	≥0.9	85V-264V
4		SPT-GS10-900-12	900	T10	12	≥960	≥0.9	85V-264V
5		SPT-GS10-1200-15	1200	T10	15	≥1200	≥0.9	85V-264V
6		SPT-GS10-1500-18	1500	T10	18	≥1440	≥0.9	85V-264V
7		SPT-GS10-1500-20	1500	T10	20	≥1600	≥0.9	85V-264V
NO.		Mode	L(mm)	Mode	Power(W)	Lumen(LM)	Power Factor	Input voltage(V)
1	PC Tube	SPT-PT10-600-6	600	T10	6	≥480	≥0.9	85V-264V
2		SPT-PT10-600-8	600	T10	8	≥640	≥0.9	85V-264V
3		SPT-PT10-900-10	900	T10	10	≥800	≥0.9	85V-264V
4		SPT-PT10-900-12	900	T10	12	≥960	≥0.9	85V-264V
5		SPT-PT10-1200-15	1200	T10	15	≥1200	≥0.9	85V-264V
6		SPT-PT10-1500-18	1500	T10	18	≥1440	≥0.9	85V-264V
7		SPT-PT10-1500-20	1500	T10	20	≥1600	≥0.9	85V-264V
8		SPT-LED Tube-Double faced	1200	T10	30	≥2400	≥0.9	85V-264V